



Yard Ramp Options



| Model | Overall Width | Inside Width | Length | Lip Section | Capacity |
|-------------------------------------|---------------|--------------|--------|-------------|-------------------------------------|
| <input type="checkbox"/> YD 70 30 | 70" | 64" | 30' | 15" | <input type="checkbox"/> 16,000 lbs |
| <input type="checkbox"/> YD 84 30 | 84" | 78" | 30' | 15" | <input type="checkbox"/> 20,000 lbs |
| <input type="checkbox"/> YD 70 36 | 70" | 64" | 36' | 15" | <input type="checkbox"/> 25,000 lbs |
| <input type="checkbox"/> YD 84 36 | 84" | 78" | 36' | 15" | <input type="checkbox"/> 30,000 lbs |
| <input type="checkbox"/> Other Size | | | | | |

* Note 36' units include level-off section

Distributed By:

W194 N11481 McCormick Drive • Germantown, WI 53022
 Phone: 262.255.1510 • Fax: 262.255.4199
Toll-Free: 800.643.5424
 or visit us on the web at...www.DockSystemsInc.com



Yard Ramps

Versatile Design For Your Portable Ramp Requirements

- Ideal For:**
- Dock to grade applications
 - Loading and unloading freight carriers
 - Loading and unloading rail cars
 - New construction sites
 - Temporary shipping yards




When only the best matters!


Portable Steel Yard Ramp



The "Tow Clamp" connects between the ramp pocket and the low hitch of your forklift truck and permits easy transportation of the lift over longer distances.



High visibility 8" yellow run-off guards.



Hydraulic adjustment system permits fast reliable height adjustment of the yard ramp with virtually any trailer bed height. Note: maximum raised height of 36 unit is 70" and 30" is 80".



72" long "level-off" section is standard on all 36' long units to permit easy access for "end-loads" and added mobility of lift trucks. Note: Longer level-off sections are available for custom applications. The shorter 30' ramp is ideal for ground to dock access applications where "level-off" is not required.



15" lip section provides for a smooth transition on and off carrier bed.



Safety chains hold the ramp tight to the carrier and assure adequate lip purchase is maintained with the carrier bed.



Heavy duty axle assembly with 18" industrial solid rubber pneumatic tires adds a high level of mobility to the yard ramp for easy positioning. Note: axle assembly can be removed or raised for permanent dock ramp installations.




Structure consists of heavy duty formed steel side girders fully welded to high strength steel joists. (Picture shows under side of ramp)



Serrated bar grating provides excellent traction. The open web design prevents build up of debris, rain, snow, oil and grease.



A 60° transition at grade and 30° transition at dock height is constructed of high strength diamond tread plate beveled and recessed for smooth transition onto and off the yard ramp.



The "ForkClamp" permits easy positioning of the ramp over short distances. Fork clamp inserts into the ramp pocket and clamps onto the fork blade.

